



model EU-1920HPS

High Polished Bottle Filler

FEATURES & BENEFITS

PUSH BUTTON

With its patented stainless steel, push-button activated valve assembly which allows for front access stream adjustment as well as cartridge and strainer access, this bottle filler offers 100% lead free waterways. The valve works at an operating pressure range of 30 to 90 psi (2.1 to 6.2 bar).

LAMINAR FLOW

Adjustable, splash-free, 1 gpm (3.78 L) laminar water flow.

EFFICIENT & FLEXIBLE INSTALLATION

Unit is designed for retrofit or new construction applications. No drain required for mounting over existing drinking fountain.

DURABLE BUILD

Good for indoor or outdoor applications (in non-freezing areas). Made with 100% Stainless Steel for vandal resistance.

CONSTRUCTION

Unit is made of 14 gauge Type 304 stainless steel with a high polished finish that resists stains and corrosion, and has soft, rounded corners. Unit features vandal-resistant bottom plate.



OPTIONS

- Mounting Plate: Model 6700 universal mounting plate for most wall mounted fountains. Priced Separately.
- Mounting Plate: Model 6700R mounting plate is used with the 1920 series bottle fillers for single or dual fountain retrofit installations.
- Back Panel: Model BP15HPS, polished stainless steel 15" back panel for Model 1920HPS.
- Back Panel: Model BP32HPS, polished stainless steel 32" back panel for model 1920HPS.

For more information, visit www.hawesco.com or call (888) 640-4297.

SPECIFICATIONS

Model 1920HPS wall mounted high-polished stainless steel bottle filler shall include 100% lead-free waterways, 1 gpm (3.8 L) laminar flow, push-button operated stainless steel valve with front-accessible cartridge and flow adjustment, and polished stainless steel wall bracket. It can be used as a stand-alone station, or mounted above the Haws® 1001HPS and 1011HPS series drinking fountains.

APPLICATIONS