



model EU-3377BFG

Bottle Filler Attachment

FEATURES & BENEFITS

QUALITY CONTROL

Pre-built fountain is pressure tested to ensure no leaks and proper functionality.

GALVANIZED FINISH

Tough galvanized coating is ideal for areas where rusting is an issue, and vandalism and graffiti could be present. Due to the galvanizing process, appearance will be a rough, unfinished galvanized surface.

PUSH BUTTON VALVE

The push-button activated valve assembly allows for front access stream adjustment as well as cartridge and strainer access. The valve works at an operating pressure range of 30 to 90 psi (2.1 to 6.2 bar).

LAMINAR FLOW

Adjustable, splash-free, 1 gpm (3.78 L) laminar water flow.

ATTACHMENT INSTALLATION

Bottle filler attachment can be ordered with a 3377 pedestal drinking fountain, or added to an existing installation.

CONSTRUCTION

Heavy-duty 3/16" (.47 cm) galvanized steel pedestal attachment is supplied with a top down access plate.



SPECIFICATIONS

Model 3377BFG bottle filler attachment for the 3377G pedestal drinking fountain shall include a 14 gauge Type 304 Stainless Steel bottle filler bracket, 3/16" galvanized steel top-access pedestal extension, 100% lead-free waterways, 1 gpm (3.8 L) laminar flow, push-button operated stainless steel valve with front-accessible cartridge and flow adjustment, and vandal-resistant bottom plate. Appearance of galvanized finish may vary. May be an accessory to a new 3377G pedestal drinking fountain or retrofit to an existing 3377G.

OPTIONS

- ❑ Bottle Filler Attachment: Model 3377BF, bottle filler attachment for the Haws 3377 pedestal fountain utilizes a satin finish stainless steel bracket, 100% lead-free waterways, laminar flow, and painted galvanized steel pedestal extension.
- ❑ Bottle Filler Attachment: Model 3377BFFR, freeze-resistant, bottle filler attachment comes with push button operation, 3/16" galvanized steel top-access pedestal extension with green powder-coated finish, and a vandal resistant bottom plate.

For more information, visit www.hawsc.com or call (888) 640-4297.

APPLICATIONS