

OPERATION

When an emergency shower or eyewash is activated, the flow of water opens a steam control valve. The steam enters a brazed plate heat exchanger, instantly heating the water. A mixing valve blends hot and cold water to produce an output of 80° F (27° C) tepid water. Additional valves keep the system preheated, freeze protected and scald protected. The steam valve will remain closed should there be a loss of water pressure.

FEATURES & BENEFITS

FLOW RATES

Provides 3 to 25 GPM (11 to 95 LPM) of tepid water.

OPERATION

Operates on typical plant steam pressure, 45 - 60 PSIG (3 - 4 BAR) is recommended. Steam and water never mix, separated by brazed plate heat exchanger. Low pressure system is available for 15 - 30 PSIG (1-2 BAR) steam.

DESIGNED TO MEET ASSE 1071 REQUIREMENTS

Unit employs a paraffin-filled thermostatic mixing element that controls the valve spool to blend exactly the correct proportions of hot and cold water to achieve the target set-point. The valve spool is treated with a special non-stick coating that minimizes buildup of minerals and particulates that can cause valve sticking. The mixing valve design allows accurate control of flow from full shower flow to the low eyewash flow ratings shown.

INSTALLATION

Ease of installation, uses existing plant saturated steam and potable water supply. Union connections are provided for quick installation. Compact, lightweight design, easily supported by pipe connections.

SERVICING

Durable, protective enclosure can be readily removed for servicing.

MEDICALLY SUPERIOR RESPONSE[®]

AXION's superior design and technology provide a complete safety solution for increased victim comfort.




SPECIFICATIONS

Model 9400 - Steam Water Heater



	MAXIMUM		MINIMUM	
Outlet Flow Rate	25 GPM	95 LPM	3 GPM	11 LPM
Ambient Operating Temperature	120°F	49°C	-30°F	-34°C
Inlet Water Pressure	90 PSIG	6 BAR	55 PSIG	4 BAR
Inlet Water Temperature	80°F	27°C	40°F	4°C
Inlet Saturated Steam Pressure	60 PSIG	4 BAR	45 PSIG	3 BAR
Saturated Steam Temperature	350°F	177°C		
Cold Water Bypass Flow Rate	24 GPM @ 25 PSI Pressure Drop			
Water Inlet & Outlet Pipe Size	1 1/4" NPT (F)			
Steam Supply & Condensate Pipe Size	1" NPT (F)			
Steam Consumption	600 lb/hr @ 25 GPM Flow Rate, 20 lb/hr @ Idle			
Condensate Discharge Rate	12 GPH maximum			
Pressure Drop Water Inlet	25 PSI @ 25 GPM			

NOTES:

1. DIMENSIONAL TOLERANCES: ±1/2".
2. RECOMMENDED WATER PRESSURE:
55 psi (3.79 bar) MIN.
90 psi (6.21 bar) MAX.
3. MODEL 9400:
RECOMMENDED SATURATED STEAM PRESSURE:
45 psi TO 60 psi (3.10 bar TO 4.14 bar)
MAXIMUM SATURATED STEAM TEMPERATURE:
350° F (177° C)
4. MODEL 9400LPS:
RECOMMENDED SATURATED STEAM PRESSURE:
15 psi TO 30 psi (1.03 bar TO 2.07 bar)
MAXIMUM SATURATED STEAM PRESSURE:
274° F (134° C) @ 30 psi (2.07 bar)
250° F (121° C) @ 15 psi (1.03 bar)



MODEL 9400 SHOWN



1456 KLEPPE LANE
 SPARKS, NEVADA 89431
 (775) 359-4712 FAX (775) 359-7424
 E-MAIL: HAWS@HAWSCO.COM
 WEBSITE: WWW.HAWSCO.COM

ECN NO. REVISED PER BY:	MODEL(S)
4930	9400/9400LPS
DATE:	DATE:
10/01/14	11/1/21
VC:	SCALE:
FV	NA
APPROVED:	DRAWING TYPE:
FV	INSTALLATION
DATE:	SIZE:
11/1/21	A
SCALE:	SHEET:
NA	1 OF 1
DRAWING TYPE:	REVISION:
INSTALLATION	11
SIZE:	PART NUMBER
A	0002080243.D
SHEET:	REVISION:
1 OF 1	11