



model EU-3377BF

Bottle Filler Attachment

FEATURES & BENEFITS

QUALITY CONTROL

Pre-built fountain is pressure tested to ensure no leaks and proper functionality.

PUSH BUTTON VALVE

The push-button activated valve assembly allows for front access stream adjustment as well as cartridge and strainer access. The valve works at an operating pressure range of 30 to 90 psi (2.1 to 6.2 bar).

LAMINAR FLOW

Adjustable, splash-free, 1 gpm (3.78 L) laminar water flow.

ATTACHMENT INSTALLATION

Bottle filler attachment can be ordered with a 3377 pedestal drinking fountain, or added to an existing installation.

CONSTRUCTION

Heavy-duty 3/16" (.47 cm) galvanized steel pedestal attachment is supplied with a top down access plate and finished with green powder-coat paint.



SPECIFICATIONS

Model 3377BF bottle filler attachment for the 3377 pedestal drinking fountain shall include a 14 gauge Type 304 Stainless Steel bottle filler bracket, and a 3/16" galvanized steel top-access pedestal extension with green powder-coated finish. It shall also include 100% lead-free waterways, 1 gpm (3.8 L) laminar flow, push-button operated stainless steel valve with front-accessible cartridge and flow adjustment, and a vandal-resistant bottom plate. May be an accessory to a new 3377 pedestal drinking fountain or retrofit to an existing 3377.

OPTIONS

- Bottle Filler Attachment: Model 3377BFG, bottle filler attachment for the Haws 3377G pedestal fountain utilizes a satin finish stainless steel bracket, 100% lead-free waterways, laminar flow, and a galvanized steel pedestal extension with no exterior treatment or processing for a rough, natural steel finish. Appearance of exterior may vary.
- Bottle Filler Attachment: Model 3377BFFR, freeze-resistant, bottle filler attachment comes with push button operation, 3/16" galvanized steel top-access pedestal extension with green powder-coated finish, and a vandal resistant bottom plate.

For more information, visit www.hawsc.com or call (888) 640-4297.

APPLICATIONS