

FEATURES & BENEFITS

GRAVITY-FED EYEWASH

Delivers ANSI-compliant eye rinsing without the need for a plumbed water connection. Ideal for temporary work areas, remote locations, or during facility maintenance.

PORTABLE AND SELF-CONTAINED

Compact and easy to relocate. The 60 liter tank supports flexible installation on walls or shelves close to hazard zones.

RELIABLE 15-MINUTE FLUSHING

Provides a consistent, gravity-fed water flow for the required 15-minute rinse, helping reduce injury from chemical or particulate exposure.

TOOL-FREE MAINTENANCE

The tank has a wide fill opening with a secure cap for easy refilling and cleaning. Includes integral carrying handles for simple handling.

SAFETY-COMPLIANT DESIGN

ABS eyewash heads include pop-off dust covers and built-in flow control. Complies with ANSI Z358.1.

OPTIONS

- Heat Shield: Model 9125 protects the tank water from overheating in hot environments. Reflects solar radiation and slows down heat absorption. Item number: 10010541
- Water Additive: Model 9082 is a bacteriostatic preservative specially formulated for use in portable eyewash units. A single 236 ml bottle treats 18.9 to 75.7 liter of potable water, helping to maintain water cleanliness and safety for up to four months. Ideal for ensuring compliance and reducing maintenance in self-contained emergency systems. 4 bottles per carton. Item number: 10000208
- Cleansing stick: Model 9083 is a long-lasting cleansing stick designed for use in portable eyewash units. It helps prevent bacterial growth — including Legionella and E. coli — as well as algae and fungi, without the use of chemicals or power. One stick keeps water clean for up to three years, offering a low-maintenance, eco-friendly solution for safe eyewash operation. Item number: 10008912

For more information, visit www.haws.ch or call + 41(0)34 420 60 00.



SPECIFICATIONS

Technical information Portable gravity-fed Eyewash 7500 (item number: 10004492)

- Flow rate eyewash: 1.5 liter/minute
- Minimum Flushing time: 15 minutes
- 60 l high-density green polyethylene tank
- Dimensions (H x W x D): 572 x 546 x 495 mm
- Meets the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment

Highlights Portable Eyewash 7500

- Bestselling portable eyewash station
- 60-liter tank provides a minimum of 15 minutes of continuous and compliant flow
- Provides safety where fixed plumbing is unavailable
- Wall or shelf mounting allows flexible positioning close to risk areas
- Easy activation via pull-down yellow spray arm
- Wide-fill cap for easy inspection, cleaning, and refilling

APPLICATIONS

The Haws® 7500 is the ideal solution for workplaces where a plumbed water supply is not available or practical.

Designed for wall or shelf mounting, this gravity-fed eyewash station provides reliable emergency rinsing in remote or temporary environments. It is particularly well suited for drilling rigs, construction and maintenance areas, remote storage locations, utility stations, and temporary job sites.

Wherever fixed plumbing is unavailable, the 7500 delivers dependable first aid to support ANSI Z358.1 compliance and maintain workplace safety standards.