

FEATURES & BENEFITS

UNIQUE AXION TECHNOLOGY

The patented AXION® Technology reliably delivers a compliant water jet for rinsing simultaneously body, eyes, and face. The unique AXION Technology eliminates the main issues of other safety shower systems to provide proper first aid.

LEAK-FREE QUALITY

The eyewash unit and valve assembly are pre-built and fully water- and pressure-tested to ensure leak-free performance and proper functionality. This reduces installation time and ensures reliable operation from day one.

ENHANCED EMPLOYEE SAFETY

The eyewash unit and valve assembly are pre-built and fully water- and pressure-tested to ensure leak-free performance and proper functionality. This reduces installation time and ensures reliable operation from day one.

COST-EFFECTIVE SAFETY SOLUTION

The eyewash made from ABS plastic, offer durability and reliability at an attractive price point. ABS plastic is impact-resistant, strong, and highly resistant to many alkalis and diluted acids, ensuring long-term functionality without increasing costs.

COMPLIANCE WITH SAFETY STANDARDS

The safety shower meets EN 15154 and ANSI Z358.1 standards, making it suitable for workplaces around the world and ensuring compliance with safety regulations.

OPTIONS

- **Dust Cover:** Model 9102 is a stainless-steel cover assembly that protects both the eyewash head and the bowl from contaminants and potential damage. Item number: 10005242
- **Foot Treadle:** Model SP220 is a foot treadle assembly that enables hands-free activation of the eyewash. Item number: 10003587
- **Instantaneous Water Heater:** Designed for indoor or outdoor applications, our CE-compliant electric water heaters deliver immediate tepid water for emergency showers and eyewashes. In line with EN 15154 and ANSI Z358.1, they ensure a continuous 15-minute flushing cycle with water maintained between 20 °C and 25 °C. This supports norm-compliant performance and helps prevent hypothermia during emergency response.

For more information, visit www.haws.ch or call + 41(0)34 420 60 00.



SPECIFICATIONS

Technical information – 7261 AXION pedestal eyewash station

- Flow rate: 14 liter/minute
- Flow pressure: min. 2.1 bar, max. 6 bar
- Static pressure: max. 8 bar
- Dimensions (H x W x D): 954 x 369 x 286 mm
- Water inlet: BSP – Rp 1/4" (EN 10226-1)
- Water outlet: BSP – Rp 1-1/4" (EN 10226-1)

Product highlights 7261 AXION

- Pre-assembled and fully water and pressure tested
- AXION technology with integrated flow control for a standard-compliant water jet
- Robust, 28 cm bowl made of high-quality ABS plastic
- Reliable chrome-plated brass ball valve with stainless steel ball and stem
- Chrome-plated brass strainer prevents suspended particles in the water from entering the eyes
- Includes universal safety sign
- Complies with standards [EN 15154](#) and ANSI Z358.1
- Wide range of options for adaptation to local requirements

APPLICATIONS

The pedestal **7261 AXION** eyewash is the ideal solution for laboratories and industrial applications where flexible placement is required. It is particularly suitable for mechanical engineering, tool manufacturing, warehouses and logistics centers, the paper industry, as well as schools, universities, and research facilities—anywhere where particularly high corrosion resistance is not necessary.

The pedestal eyewash complies with the international standards EN 15154-2 and ANSI Z358.1 and, with its patented AXION® showerhead, guarantees a standard-compliant water jet for efficient flushing of the eyes and face.