



# model EU-3377BFFR

## Bottle Filler Attachment

### FEATURES & BENEFITS

#### **PUSH BUTTON**

Polished chrome-plated push-button requires less than 5 lbs. (2.7 kg) of push force to activate.

#### **FREEZE-RESISTANT VALVE**

Fully engineered system with the pneumatic operated freeze-resistant valve installed below frost line to drain water to non-freezing depth allowing fountain to function year-round. Assembly can be lifted to surface and lowered back into casing for easy maintenance without disturbing the fountain.

#### **LAMINAR FLOW**

Adjustable, splash-free, 1 gpm (3.78 L) laminar water flow.

#### **ATTACHMENT INSTALLATION**

Bottle filler attachment can be ordered with a 3377 pedestal drinking fountain, or added to an existing installation.

#### **CONSTRUCTION**

Heavy-duty 3/16" (.47 cm) galvanized steel pedestal attachment is supplied with a top down access plate and finished with green powder-coat paint.



### SPECIFICATIONS

Model 3377BFFR freeze-resistant bottle filler attachment for the 3377FR pedestal drinking fountain shall include a 14 gauge Type 304 Stainless Steel bottle filler bracket, and a 3/16" galvanized steel top-access pedestal extension with green powder-coated finish, polished chrome-plated brass push-button, and vandal-resistant bottom plate. May be an accessory to a new 3377FR pedestal drinking fountain or retrofit to an existing 3377FR. REQUIRES MODEL 6518.2FR PRICED SEPARATELY.

### OPTIONS

For more information, visit [www.hawsc.com](http://www.hawsc.com) or call (888) 640-4297.

### APPLICATIONS

